

M A T E R I A L S A F E T Y D A T A S H E E T

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : CAMIE 480 SCREEN OPENER DATE PRINTED: 02/11/00
 IDENTIFICATION NUMBER: FCC0480
 PRODUCT USE/CLASS :

SUPPLIER: Camie-Campbell
 9225 Watson Industrial Park
 St. Louis, MO 63126
 MANUFACTURER: Camie-Campbell
 9225 Watson Industrial Park
 St. Louis, MO 63126
 EMERGENCY TELEPHONE: 800-424-9300 EMERGENCY TELEPHONE: 800-424-9300
 24 HOUR EMERGENCY PHONE 24 HOUR EMERGENCY PHONE

PREPARED: JIM, PHONE: 314/968-3222, PREPARE DATE: 02/11/00
 REPLACES DATE: 08/18/97

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	LIGHT AROMATIC SOLVENT NAPHTHA	64742-95-6	35.0 %
02	CYCLOHEXANONE	108-94-1	20.0 %
03	ISOBUTANE	75-28-5	20.0 %
04	PSEUDOCUMENE	95-63-6	20.0 %
05	PROPANE	74-98-6	15.0 %
06	O-XYLENE	95-47-6	5.0 %
07	CUMENE	98-82-8	5.0 %

ITEM	TLV-TWA	EXPOSURE LIMITS				SKIN
		ACGIH	OSHA	PEL-TWA	PEL-CEILING	
01	NO INFO	NO INFO	NO INFO	NO INFO	NO INFO	NO
02	25 PPM	NO INFO	NO INFO	NO INFO	NO INFO	NO
03	NO INFO	NO INFO	NO INFO	NO INFO	NO INFO	NO
04	NO INFO	NO INFO	NO INFO	NO INFO	NO INFO	NO
05	2500 PPM	NO INFO	NO INFO	NO INFO	NO INFO	NO
06	NO INFO	NO INFO	NO INFO	NO INFO	NO INFO	NO
07	NO INFO	NO INFO	NO INFO	NO INFO	NO INFO	NO

SECTION 3 - HAZARDS IDENTIFICATION

*** EMERGENCY OVERVIEW ***: THIS PRODUCT CONTAINS COMPONENTS WHICH MAY CAUSE ADVERSE REPRODUCTIVE AND/OR DEVELOPMENTAL EFFECTS. PREGNANT WOMEN

(Continued on Page 2)

Product: FCC0480 Preparation Date: 02/11/00 Page 2

SECTION 3 - HAZARDS IDENTIFICATION

MAY BE AT AN INCREASED RISK FROM EXPOSURE. KEEP FROM REACH OF CHILDREN. DO NOT PUNCTURE, INCINERATE, OR PLACE AEROSOL PRODUCT CONTAINERS IN COMPACTORS. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN MUST BE OBSERVED. DO NOT FLAME CUT, BRAZE, OR USE WELDING TORCH. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THIS PRODUCT MAY BE HARMFUL OR FATAL.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION DEBRITTING, DERMATITIS.

EFFECTS OF OVEREXPOSURE - INHALATION: EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS, AND EVEN ASPHYXIATION. OVEREXPOSURE MAY CAUSE DAMAGE TO THE NERVOUS SYSTEM.

EFFECTS OF OVEREXPOSURE - INGESTION: No Information.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: OVEREXPOSURE TO THIS MATERIAL (OR ITS COMPONENTS) HAS APPARENTLY BEEN FOUND TO CAUSE THE FOLLOWING EFFECTS IN LABORATORY ANIMALS: KIDNEY DAMAGE, LIVER DAMAGE, OVEREXPOSURE TO THIS MATERIAL (OR ITS COMPONENTS) HAS APPARENTLY BEEN FOUND TO CAUSE THE FOLLOWING EFFECTS IN HUMANS: LIVER DAMAGE, KIDNEY DAMAGE, SPLEEN DAMAGE, PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INHALATION EYE CONTACT

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. LAUNDRY CONTAMINATED CLOTHING BEFORE RE-USE. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

FIRST AID - INHALATION: REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. GIVE ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. KEEP PERSON WARM AND QUIET. GET MEDICAL ATTENTION.

FIRST AID - INGESTION: DO NOT INDUCE VOMITING. GIVE TWO GLASSES OF WATER IF CONSCIOUS. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GET IMMEDIATE MEDICAL ATTENTION.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: -156 F LOWER EXPLOSIVE LIMIT: 0.9 %
 (PENSKY-MARTENS C.C.) UPPER EXPLOSIVE LIMIT: 9.5 %

(Continued on Page 3)

SECTION 5 - FIRE FIGHTING MEASURES

AUTOIGNITION TEMPERATURE: N.D.
EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: VAPORS ARE HEAVIER THAN AIR AND TRAVEL ALONG THE GROUND OR MAY BE MOVED BY VENTILATION AND IGNITED BY IGNITION SOURCES AT LOCATIONS DISTANT FROM MATERIAL HANDLING POINT. FOR AEROSOL PRODUCTS - EXPOSURE TO TEMPERATURES OVER 130F MAY CAUSE CONTAINERS TO BURST, RELEASING HIGHLY FLAMMABLE GAS.

SPECIAL FIREFIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN FIGHTING FIRES. KEEP FIRE EXPOSED CONTAINERS COOL WITH WATER FOG. RESPIRATORY, LIVER, KIDNEY, DERMAL ILLMENTS,

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ELIMINATE SOURCES OF IGNITION & VENTILATE AREA. PERSONS NOT PROPERLY EQUIPPED SHOULD BE EXCLUDED FROM AREA. STOP SPILL AT SOURCE - PREVENT SPREADING. AVOID INHALATION OF VAPORS. AVOID SKIN CONTACT WITH LIQUID. SOAK UP ON ABSORBING MATERIAL AND PLACE INTO PROPER CONTAINER FOR DISPOSAL. USE NON-SPARKING SCOOPS FOR FLAMMABLE MATERIALS. CLEAN WALKING SURFACES THOROUGHLY TO REDUCE SLIPPING HAZARD.

SECTION 7 - HANDLING AND STORAGE

HANDLING: No Information.

STORAGE: DO NOT STORE ABOVE 120F. DO NOT STORE IN DIRECT SUNLIGHT. KEEP AWAY FROM HEAT SOURCES, OPEN FLAME, SPARKS. DO NOT STORE ABOVE 120F. DO NOT STORE IN DIRECT SUNLIGHT.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: PROVIDE SUFFICIENT MECHANICAL VENTILATION (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

RESPIRATORY PROTECTION: IF WORK PLACE EXPOSURE LIMITS OF PRODUCT OR ANY COMPONENT IS EXCEEDED, USE A NIOSH/MSHA APPROVED RESPIRATOR. CONSULT YOUR SAFETY EQUIPMENT SUPPLIER FOR RECOMMENDATIONS.

SKIN PROTECTION: WEAR IMPERVIOUS GLOVES IF METHOD OF USE INVOLVES SKIN CONTACT WITH PRODUCT. CONSULT YOUR SAFETY SUPPLY VENDOR FOR GLOVE RECOMMENDATIONS.

EYE PROTECTION: WEAR SAFETY GLASSES AT MINIMUM, MORE EXTENSIVE PROTECTION MAY BE NECESSARY DEPENDING ON HOW THE PRODUCT IS TO BE USED.

(continued on Page 4)

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

OTHER PROTECTIVE EQUIPMENT: WEAR IMPERVIOUS CLOTHING IF BODILY EXPOSURE IS ANTICIPATED. CONSULT YOUR SAFETY SUPPLY VENDOR FOR RECOMMENDATIONS.

HYGIENIC PRACTICES: WASH HANDS BEFORE EATING OR SMOKING. SMOKE IN DESIGNATED AREAS ONLY. REMOVE AND LAUNDRER CLOTHING IF CONTAMINATED.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE : -44 - 410 F VAPOR DENSITY : Is heavier than air
ODOR : PUNGENT ODOR THRESHOLD : N.D.
APPEARANCE : CLEAR LIQUID EVAPORATION RATE: Is faster than Butyl acetate
SOLUBILITY IN H2O : NEGLIGIBLE
FREEZE POINT : N.D.
VAPOR PRESSURE : N.D. PH @ 0.0 % : N.A.
PHYSICAL STATE : LIQUID VISCOSITY : N.D.
COEFFICIENT OF WATER/OIL DISTRIBUTION: N.D.

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: HEAT, SPARKS, WELDING ARCS, OPEN FLAME, STATIC ELECTRICITY, OR OTHER SOURCE OF IGNITION.

INCOMPATIBILITY: OXIDIZING AGENTS. STRONG OXIDIZERS,

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE AND CARBON DIOXIDE. SULFUR DIOXIDE, NITROGEN OXIDE, NITROGEN PEROXIDE,

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

(Continued on Page 5)

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Aerosols
DOT TECHNICAL NAME:
DOT HAZARD CLASS: 2.1 HAZARD SUBCLASS: NONE
DOT UN/NA NUMBER: UN1950 PACKING GROUP: NONE RESP. GUIDE PAGE: 126

ADDITIONAL INFORMATION: FOR DOMESTIC GROUND AND AIR SHIPMENT THIS PRODUCT MAY BE SHIPPED AS A CONSUMER COMMODITY ORM-D. OUTER CARTONS MUST HAVE THE ORM-D OR ORM-D AIR DESIGNATION. (OUR ORIGINAL CARTONS ARE PREPRINTED WITH THE ORM-D DESIGNATION FOR GROUND SHIPMENT)

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -
OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:
This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD FIRE HAZARD PRESSURIZED GAS HAZARD

SARA SECTION 313:
This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME	CAS NUMBER	WT/WT %	IS LESS THAN
PSEUDOCUMENE	95-63-6		20.0 %
O-XYLENE	95-47-6		5.0 %
CUMENE	98-82-8		5.0 %

TOXIC SUBSTANCES CONTROL ACT:
This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

CHEMICAL NAME CAS NUMBER
No information is available.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.
CANADIAN WHMIS CLASS: No information available.

(Continued on Page 6)

SECTION 15 - REGULATORY INFORMATION

ON JUNE 30, 1993 THE OSHA 2-1-A TABLE WAS REVOKED AND OSHA REVERTED BACK TO THEIR PRIOR EXPOSURE LIMITS. THE VALUES ON THIS MSDS REFLECT THE ROLL BACK TO THE PRIOR VALUES. SOME STATES MAY CONTINUE TO ENFORCE THE 1993 LIMITS.

SECTION 16 - OTHER INFORMATION

HMS RATINGS - HEALTH: 3 FLAMMABILITY: 4 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 08/18/97

REASON FOR REVISION: SCHEDULED UPDATE

VOC CONTENT: 100.0 % BY WEIGHT, 754 GRAMS/LITER TOTAL PRODUCT.

754 GRAMS/LITER LESS WATER AND EXEMPT, 0.95 LBS/CAN

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

The information contained on this MSDS is been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and local laws and regulations. The environmental information and hazardous materials identification system have been included by Camie-Campbell Inc. in order to provide additional health and hazard classification information. The ratings recommend are based upon the criteria supplied by the developers of these rating systems, together with Camie-Campbell Inc.'s interpretation of the available data. Proper personal protective equipment varies widely with conditions of use and anticipated exposure. We recommend that a supervisor or other qualified person determine proper PPE for intended use.

<END OF MSDS>